

# Twin State Speedway's 2012 Open Enduro Racing Guide lines /Rules

**If it is not listed below do not do it. These cars must be O.E.M. stock for make, model, year, and V.I.N number. No Performance parts**

## **Eligible Models:**

1. Any American or Foreign made four seater, 4-6-or 8 cylinder hard top sedan, station wagons or lift backs. No sports cars, turbocharged, four wheel or all wheel drive. Camaros and Mustangs are allowed.

## **VIN And OBD:**

1. All cars must be completely OEM stock with the VIN number and OBD in place.

## **Windshield:**

1. All cars must have an O.E.M., clear lexan, or heavy wire mesh over the entire windshield area.

## **Miscellaneous:**

1. All other glass, hard plastics, moldings, trim, outside mirrors, and airbags must be removed.

## **Doors/Bumpers/Exhaust/ Lift Chain:**

1. All doors must be welded, chained or bolted. Door latches must be left O.E.M. stock.
2. All bumpers must be O.E.M. A min. 5/16" chain must be attached from the bumper to the frame in the front and back to keep the bumpers from falling off in case of impact.

## **Hood:**

1. All hoods must have at least two quick release hood pins or a two foot hole cut in it.

## **Tires/Camber:**

1. **All tires must be D.O.T with a minimum tread wear of 400. The 400 must be clearly marked.**
2. **The second number of all tires can be no smaller than 60. This means a 59 is illegal.**
3. **All four tires must be the same size. A maximum of 1" camber allowed on the right front.**

## **Seat Area:**

1. Seat belts, shoulder straps, helmet, eye protection, long sleeve shirt, and full length pants are mandatory.
2. A piece of tubing with a minimum O.D. of 1-3/4" is mandatory behind the driver's seat. This tubing must be close to the seat. The tubing must be welded solidly to the driver's side and the passenger's side of the car.
3. A plate must be welded to both ends of the tubing. The plate must be a minimum of 1/4" thick by 3"x3".