

Twin State Speedway's 2012 Red Neck Racing Guide lines /Rules

If it is not listed below do not do it. These cars must be O.E.M. stock for make, model, year, and V.I.N number.

Any car that is dominant weekly will receive a weight penalty. The weight will have a specific placement.

Eligible Four Cylinder models:

1. Dodge Neon, 2.0.
2. Ford Escort and Focus, 1.9 and 2.0.
3. G.M., Cavalier and Sunfire, 2.0 and 2.2.
4. Other models may be approved by Management. Ask before you build.

Eligible Six Cylinder models:

1. Dodge, 3.0.
2. Ford Taurus, 3.0.
3. G.M. Malibu, Century, and Lumina, 3.1.
4. Other models may be approved by Management. Ask before you build.

Paint:

1. All four cylinders must paint their roof Red.
2. All six cylinders must paint their roof Green.

VIN And OBD:

1. All cars must be completely stock with the VIN number in place and OBD in place.

Windshield:

1. All cars must have the O.E.M. windshield, clear lexan, or heavy wire mesh over the complete windshield area.

Miscellaneous:

1. All other glass, hard plastics, moldings, outside mirrors and airbags must be removed.

Doors/Bumpers/Exhaust/ Lift Chain:

1. Door latches must be left O.E.M. stock.
2. All doors must be welded or chained.
3. All bumpers must be O.E.M. style.
4. A min. 5/16" lift chain must be attached to the frame in the front and back for lifting.
5. The exhaust may exit through the hood or under the car beyond the driver's seat.

Hood/ Trunk:

1. All hoods must have at least two quick release hood pins on the front.
2. All trunks lids except hatch back cars must have at least two quick release hood pins on the rear of them.

Tires:

1. All tires must be D.O.T with a minimum tread wear of 400. The 400 must be clearly marked with paint..
2. All four tires must be the same size.
3. The second number of all tires can be no smaller than 60. **This means a 59 is illegal.**

Seat Area:

1. Seat belts, shoulder straps, window net, helmet, eye protection, long sleeve shirt, and full length pants are mandatory.
2. A piece of tubing with a minimum O.D. of 1-3/4" is mandatory behind the driver's seat. This tubing must be close to the seat.
3. The tubing must be welded solidly to the driver's side and the passenger's side of the car.
4. A plate must be welded to both ends of the tubing. The plate must be a minimum of 1/4" thick by 3"x3".

Race Distance:

1. The race will go a distance to be posted at the Handicap tower weekly.
2. The race will go the scheduled laps to the right and then to the left with a minimum of one scheduled weekly race between them. GBDF2011